



HIGHLIGHTS INTEGRATED

LDsystems 

Designed in Germany, **integrated** around the world!

LD Systems® – Your Sound. Our Mission.

As a user of professional audio technology, you are in good hands with LD Systems. Your enthusiasm is our benchmark. Whether you are a system integrator, a sound engineer, a mobile DJ, a musician, a band, a singer-songwriter, a wedding singer or fitness trainer or just a sound addict like us – your needs are at the heart of every decision we make.

We are passionate about developing professional audio solutions that make your life easier on the job and meet your high expectations for sound and performance.

Of course, we are also happy to support you beyond your purchase. With us, you'll experience some of the best customer support in the industry – true to the motto "Your Sound. Our Mission."

LD Systems' professional audio product lines include innovative, high-performance PA systems, advanced speakers and subwoofers for live events, installations, battery-powered or outdoor use.

LD Systems wireless microphone and in-ear monitoring systems provide full freedom of movement and reliability for artists on stage and excellent speech intelligibility for speakers in conferences.



DQOR[®] SERIES

04



CURV 500[®] SERIES

06



MAUI[®] SERIES

12



MAILA[®] SERIES

14



TICA[®] SERIES

16



IMA[®] SERIES

18



IPA SERIES

20



ZONEX SERIES

22



U500[®] SERIES

24



QUESTRA[®]

28



CONTRACTOR[®] SERIES

30

DQOR[®] SERIES

Sounds as good as it looks.

TWO-WAY PASSIVE INDOOR/OUTDOOR INSTALLATION LOUDSPEAKER

Encourage your customers and guests to linger for longer with great sound. Thanks to their wide coverage angle and balanced sound, DQOR speakers provide an inviting ambience whether indoors or outdoors. These modern and dynamic looking installation speakers are available as 3", 5" and 8" versions in black or white and respectively with two connection variants: low impedance (8 Ohm), or high impedance (70V/100V/16 Ohm) with multiple power taps.



reddot winner 2021

INDOOR AND OUTDOOR USE
IP65 (DQOR 3) AND IP55 (DQOR 5 & 8)
CERTIFIED

ELEGANT, DYNAMIC DESIGN
TO SUIT ANY ENVIRONMENT

SLIDE-AND-LOCK WALL MOUNT
WITH CONCEALED CONNECTIONS

CORROSION-RESISTANT FRONT GRILLE
FOR EFFECTIVE PROTECTION

**AVAILABLE IN BLACK
AND WHITE**

TWO CONNECTION VARIANTS
LOW IMPEDANCE (8 OHM)
AND 70/100V VERSION

FLEXIBLE POSITIONING
DUE TO TILT ANGLE OF UP TO
27° AND 45° HORIZONTAL
SWIVEL ANGLE





DQOR® 3 (W)

3" TWO-WAY PASSIVE INDOOR/OUTDOOR
 INSTALLATION LOUDSPEAKER

Load rating (RMS)	30 W
Max. SPL (Peak)	98 dB
Frequency response (-10 dB)	85 - 20,000 Hz
Dimensions (W x H x D)	114.6 x 180 x 180.8 mm 4.5 x 7.1 x 7.1 inch
Weight	1.4 kg / 3.1 lbs



DQOR® 5 (W)

5" TWO-WAY PASSIVE INDOOR/OUTDOOR
 INSTALLATION LOUDSPEAKER

Load rating (RMS)	70 W
Max. SPL (Peak)	105 dB
Frequency response (-10 dB)	74 - 20,000 Hz
Dimensions (W x H x D)	156.7 x 253.8 x 215.3 mm 6.2 x 10 x 8.5 inch
Weight	2.7 kg / 5.95 lbs



DQOR® 8 (W)

8" TWO-WAY PASSIVE INDOOR/OUTDOOR
 INSTALLATION LOUDSPEAKER

Load rating (RMS)	120 W
Max. SPL (Peak)	109 dB
Frequency response (-10 dB)	62 - 20,000 Hz
Dimensions (W x H x D)	255.8 x 413.9 x 314.6 mm 10.1 x 16.3 x 12.4 inch
Weight	5.2 kg / 11.5 lbs

EASY INSTALLATION

AVAILABLE IN BLACK AND WHITE

Wall Mount (included)

- Slide-and-lock wall mount mechanism
- With concealed integrated connections
- Optional wall mount cover



Pole Mount Bracket

Pole Mount Bracket

- For mounting on cylindrical objects (poles, trusses, etc.)
- Maximum load capacity: 20 kg

Cluster Mount Bracket

- For ceiling or floor mounting
- Including safety lugs to secure the mounted speakers
- Maximum load capacity (centered): 50 kg



Cluster Mount Bracket



CURV 500[®] SERIES

An array of possibilities

Flexible, scalable array with WaveAhead[®] technology and expandable vertical coverage for amazing sound pressure and excellent balance. Constructed around our SmartLink[®] plug-and-play adapter, numerous mounting solutions are offered, including optional extensions and additional coverage control.



red dot award 2016
winner



**ELEGANT UNIBODY
ALUMINIUM HOUSING**

**NARROW 10° VERTICAL DISPERSION
(PER SATELLITE)** FOR REDUCTION OF
REFLECTIONS ON CEILINGS AND FLOORS


**WIDE DISPERSION OF MID
AND HIGH FREQUENCIES**

WAVEAHEAD[®] TECHNOLOGY
SYMMETRICAL HORIZONTAL DISPERSION

SMARTLINK[®] ADAPTER
FOR WIRELESS CONNECTION OF
UP TO FOUR ARRAY SATELLITES



**CUSTOMIZABLE
IN ANY RAL COLOUR**



Find out more about our **CURV 500[®] SERIES**
[id-systems.com/CURV500](https://www.id-systems.com/CURV500)





CURV 500® I SUB (W)

10" INSTALLATION SUBWOOFER

Load rating (RMS)	200 W
Sensitivity	approx. 87dB 1W/1m
Frequency Response	47 -150 Hz
Dimensions (W x H x D)	610 x 310 x 230 mm 24 x 12.2 x 9 inch
Weight	14.5 kg / 32 lbs



CURV 500® S2 (W)

TWO ARRAY SATELLITES

Load rating (RMS)	40 W
Max. SPL	104 dB
Woofers	3 x 1" tweeter / 1 x 4" mid
Dimensions (W x H x D)	122 x 122 x 122 mm 4.8 x 4.8 x 4.8 inch
Weight (Pair)	3.44 kg / 7.6 lbs



CURV 500® D SAT (W)

DUPLEX SATELLITE

Load rating (RMS)	80 W
Max. SPL (Peak)	110 dB
Woofers	6 x 1" tweeter / 2 x 4" mid
Dimensions (W x H x D)	122 x 240 x 126 mm 4.8 x 9.4 x 4.96 inch
Weight	3.3 kg / 6.6 lbs



CURV 500® SLA T (W)

70 / 100 V SMARTLINK® ADAPTER


Connectors	1x Phoenix 1x Speakon compatible
Features	2 x 16 mm flanges, 2x M6 thread (optional wall mount)
Dimensions (W x H x D)	122 x 57 x 57 mm 4.8 x 2.2 x 2.2 inch
Weight	0.35 kg / 0.77 lbs



CURV 500® I AMP

4-CHANNEL CLASS D INSTALLATION AMPLIFIER

Rated output power	1kHz @ 2,7 Ohms: 4 x 240 W; 1kHz @ 4 Ohms: 4 x 240 W; 1kHz @ 8 Ohms: 4 x 120 W; 1kHz @ 16 Ohms: 4 x 60 W
Frequency response	10 - 22000 Hz
Max. Power consumption	1100 W
Dimensions (W x H x D)	482 x 44 x 420 mm 19 x 1.7 x 16.5 inch
Weight	6.8 kg / 15 lbs



CURV 500® WMBL (W)

TILT & SWIVEL WALL MOUNT BRACKET



CURV 500® WMB (W)

WALL MOUNTING BRACKET FOR CURV 500 SATELLITES





CURV 500® CMB (W)

CEILING MOUNTING BRACKET FOR CURV 500 SATELLITES



CURV 500® TMB

TRUSS CLAMP FOR CURV 500 SATELLITES




CURV 500® SERIES

BISTRO


Bistros, cafés, clubs or restaurants often require audio systems with a multi-zone layout. The modular design of the **CURV 500®** installation system enables individual configurations for each zone ranging from subtle background music to dancefloor levels while keeping the same excellent sonic signature throughout the installation.

BISTRO MEDIUM BUNDLE 12 SATELLITES AND 2 SUBWOOFERS


ZONE 1



CH A PRESET: 2xC500-SAT




CH B PRESET: 1xC500ISUB




CURV 500® I AMP OUTPUT
4 balanced mono line inputs, assignable to any output, in any combination, thanks to the internal routing matrix.

ZONE 2



CH C PRESET: 2xC500-SAT



CH D PRESET: 1xC500ISUB


INSTALL SOLUTIONS

CONFERENCE

In addition to excellent speech intelligibility, conference and meeting room audio systems must deliver superb sound reproduction for multimedia applications. With its modular design and elegant appearance, the **CURV 500®** is the perfect choice for all installation sizes from small meeting rooms to large multipurpose spaces.

CONFERENCE MEDIUM BUNDLE 8 SATELLITES AND 1 SUBWOOFER

FRONT



CURV 500® I AMP OUTPUT

4 balanced mono line inputs, assignable to any output, in any combination, thanks to the internal routing matrix.

REAR




CURV 500[®] SERIES

VOICE


Audio installations for speech reproduction like for house of worship - or corporate boardroom applications typically do not require sub frequency reinforcement, however subwoofers are offered for the CURV installations where sub frequencies are needed. The **CURV 500[®]** system's **I AMP** provides delay compensation per channel to ensure maximum speech intelligibility, imaging and sound quality throughout the installation.

VOICE MEDIUM BUNDLE 24 SATELLITES

ZONE 1



CH A PRESET: 3xC500-SAT




CH B PRESET: 3xC500-SAT




CURV 500[®] I AMP OUTPUT
4 balanced mono line inputs, assignable to any output, in any combination, thanks to the internal routing matrix.

ZONE 3



CH C PRESET: 3xC500-SAT



CH D PRESET: 3xC500-SAT

INSTALL SOLUTIONS


70V EXAMPLE

The **CURV 500® I AMP** includes 70V output to deliver audio to a large number of speakers.

This permits setting up a distributed system by daisy-chaining a maximum of 24 satellites to bridged channel A and B outputs, or bridged channel C and D outputs. The satellites can be wired individually or in groups of 2, 3 or 4 units.

70V EXAMPLE - 3 SATELLITE SETS MAX. 24 SATELLITES PER BRIDGED OUTPUT

ZONE 1 - SATELLITES




CH A PRESET: 3xC500-70V



CURV 500® I AMP OUTPUT

4 balanced mono line inputs, assignable to any output, in any combination, thanks to the internal routing matrix.

ZONE 1 - SUBWOOFERS



MAUI® SERIES – Sleek. Easy. Mighty.

The MAUI® Series by LD Systems is an innovative audio solution designed to elevate your indoor install projects to new heights. With cutting-edge technology and a perfect blend of engineering excellence, this state-of-the-art system delivers exceptional audio performance.

Experience the power of pristine sound quality with advanced WaveGuide®

technology, providing wide horizontal coverage and focused vertical dispersion. Whether it's background music, engaging presentations, or clear speeches, the Maui Series ensures every corner of your venue is filled with immersive audio. It seamlessly blends into any environment, adding a touch of sophistication while delivering powerful sound.



reddot winner 2021

BEM-OPTIMIZED HIGH FREQUENCY WAVEGUIDE
FOR WIDE HORIZONTAL AND CONTROLLED VERTICAL DISPERSION

U-BRACKET INCLUDED
BRACKET FOR ANGLED WALL INSTALLATION OPTIONALLY AVAILABLE

**ALL MAUIS AVAILABLE
IN BLACK OR WHITE**

MAUI® i1

IP65 PROTECTION CLASS
ALUMINUM SPEAKER GRILLE AND WEATHER TREATED CONES

4-POLE TERMINAL BLOCK CONNECTOR
FOR PARALLEL SPEAKER CONNECTION

INPUT SELECTOR SWITCH 8 OHMS
(TRANSFORMER BYPASS) / 100 V / 70 V




Find out more about our **MAUI®** SERIES
ld-systems.com/MAUI



MAUI® i1

PASSIVE INDOOR/OUTDOOR INSTALLATION
COLUMN LOUDSPEAKER

System power (Peak)	480 W
Max. SPL (Peak)	116 dB
Woofers	9 x 3" mid / low
Overall height	985 mm / 38.8 inch
70 V / 100 V power taps	60 W, 30 W, 15 W, 7.5 W



MAUI® i1 WMBT

TILT-AND-SWIVEL WALL MOUNT FOR MAUI® i1,
BLACK AND WHITE

Swivel	160°
Tilt	40°, continuously variable
Material	Powder-coated steel
Max. load capacity	20 kg / 44.1 lbs
Weight	1.5 kg / 3.3 lbs



40° tilt



160° swivel



MAUI® 28 G3

COMPACT POWERED COLUMN PA SYSTEM

System power (Peak)	2060 W
Max. SPL (Peak)	127 dB
Woofers	2 x 1" tweeter / 12 x 3.5" mid / 12" sub
Overall height	2052 mm / 80.8 inch
Weight	35.4 kg / 78 lbs



MAUI® 11 G3

PORTABLE POWERED COLUMN PA SYSTEM

System power (Peak)	1460 W
Max. SPL (Peak)	125 dB
Woofers	2 x 1" tweeter / 6 x 3.5" mid / 2 x 8" sub
Overall height	2052 mm / 80.8 inch
Weight	30.7 kg / 67.7 lbs



MAUI® P900 (W/G/B)

POWERED COLUMN PA SYSTEM
BY PORSCHE DESIGN STUDIO

System power (Peak)	2800 W
Max. SPL (Peak)	131 dB
Woofers	32 x 1" tweeter / 16 x 2.8" mid / 2 x 10" sub
Overall height	2173 mm / 85.6 inch
Weight	46 kg / 101.4 lbs




MAILA® SERIES

MODULAR ALL-ROUND INTELLIGENT LINE-ARRAY

MAILA® is not just "one" product, but a scalable sound reinforcement system that sets new standards in its diversity and flexibility. From a wedding reception to a conference to a festival - MAILA combines the best concepts of sound reinforcement technology in one system. Also, with the EasySplay® mechanism and many other clever features, MAILA takes user-friendliness in the line array sector to a whole new level. The result is a big, scalable sound for almost any application.



reddot winner 2023



LogoLink® HIDDEN ANTENNA
FOR SAFE WIRELESS CONNECTION

IDENTIFICATION LED
FOR IDENTIFYING DEVICES

SMARTLINK+®
ELEGANT CABLE-
FREE CONNECTION

**CONNECT UP TO
8 SATELLITES**
IN FLOWN SETUPS

EASYSPLAY®
EASY ONE-HAND SPLAY
ANGLE ADJUSTMENT

**TOOL-LESS TRUSS
MOUNTING WITH
EASYMOUNT+®**



Find out more about our **MAILA® SERIES**
id-systems.com/MAILA



MAILA® S MAILA® M MAILA® L

THE FOUR MAILA® MODULES



MAILA® SAT

PASSIVE ARRAY SATELLITE SPEAKER

Frequency response (-6 dB)	100 - 20,000 Hz
Load rating (AES)	175 W / 50 W
Max. SPL Peak (Pink noise)	129.1 dB (fullspace @1m, Crest factor 4)
Connectivity	SmartLink+®
Dimensions (W x H x D)	205 x 234 x 226 mm 8.1 x 9.2 x 8.9 inch
Weight	7.65 kg / 16.9 lbs



MAILA® SPA

AMPLIFIER FOR UP TO EIGHT SATELLITES

Frequency response (-6 dB)	-
Amplifying power	1.25 kW RMS
Connectivity	SmartLink+®, XLR, LogoLink®
Dimensions (W x H x D)	205 x 282 x 226 mm 8.1 x 11.1 x 8.9 inch
Weight	7.45 kg / 16.4 lbs



MAILA® COL

POWERED 4 X 6.5" COLUMN SPEAKER AND AMPLIFIER

Frequency response (-6 dB)	105 Hz - 500 Hz
Amplifying power	2.5 kW RMS
Max. SPL Peak (Pink noise)	130 dB (fullspace @1m, Crest factor 4)
Connectivity	SmartLink+®, XLR, LogoLink®
Dimensions (W x H x D)	205 x 1028 x 354 mm 8.1 x 40.5 x 13.9 inch
Weight	36.195 kg / 79.8 lbs



MAILA® SUB

POWERED DUAL 15" BANDPASS SUBWOOFER

Frequency response (-6 dB)	33 Hz - Preset
Amplifying power	2.5 kW RMS
Max. SPL Peak (Pink noise)	131 dB (fullspace @1m, Crest factor 4)
Connectivity	XLR, LogoLink®
Dimensions (W x H x D)	540 x 934 x 803 mm 21.3 x 36.8 x 31.6 inch
Weight	89.8 kg / 198 lbs

MAILA APP FOR FAST SETUP

- **Room simulation:** Automatic EQ adjustment and calculation of the splay angles
- **Pre-planning:** Optimal preparation in advance, no matter when and where
- **10 Band EQ Presets:** Create custom 10-band parametric EQ presets
- **Delay lines:** Easy delay line configuration based on distance and temperature



TICA® SERIES

TOOLS FOR INTEGRATING COMMERCIAL AUDIO

Flexible and affordable professional audio solutions! The TICA® series offers a versatile range of products that seamlessly integrate in both smaller and larger audio setups. TICA® stands as a testament to thoughtful engineering, enabling users to customize their audio systems by mixing and matching components to meet specific needs. Experience unparalleled flexibility and exceptional features without breaking the bank with the TICA® Series!




PREAMP/MIXER FOR COMBINING
ANNOUNCEMENTS AND MUSIC

**RACK-, CEILING-, TABLE- OR
BEHIND-SCREEN MOUNTING**

BESPOKE AUDIO SYSTEM IN 1U RACK
DUE TO 1/3 OR 1/4 RACK WIDTH OF EACH DEVICE

TIME-BASED AUDIO SCHEDULING
WITH REMOTE DEVICE CONTROL



Find out more about our TICA® SERIES
[id-systems.com/TICA](https://www.id-systems.com/TICA)





AMP 106 T

1-CHANNEL MINI INSTALLATION POWER
AMPLIFIER 60 W @ 4 OHM / 70V / 100V

Size	1/4 19" rack, 1U
Line Inputs	2
Powered Outputs	1 with output mode selector (Low-Z/High-Z)
RMS Power	60 W (Continuous sine wave 1kHz, 4 ohm load)
Third Party/Remote Control	Standby, VCA



Dante

AMP 205 (D/AV)

2-CHANNEL MINI INSTALLATION POWER
AMPLIFIER 2X50 W @ 4 OHM, DANTE MODEL:
WITH DANTE INTERFACE, AV MODEL: WITH HDMI INTERFACE

Size	1/3 19" rack, 1U
Line Inputs	2
Powered Outputs	2
RMS Power	1 x 100 W @ 2ohm (Continuous sine wave 1kHz 10sec, 4 ohm load), 2 x 50 W @ 4ohm (ST, PAR)
Third Party/Remote Control	Standby, VCA



Dante

DIO (04/22/44)

4 OUTPUT / 2X2 INPUT/OUTPUT /
4X4 INPUT/OUTPUT DANTE INTERFACE

Size	1/3 19" rack, 1U
Line Inputs	0 / 2 / 4 (terminal block)
Third Party/Remote Control	Ethernet Control / QUESTRA Control
Line Outputs	4 / 2 / 4 (terminal block)
Gain Steps	-15dB, 0dB, +15dB, +30dB



RSMP

RADIO STREAMING MEDIA PLAYER

Size	1/3 19" rack, 1U
Remote Control	UNDOK App Control
Audio modes	Audio Streaming services, Bluetooth Audio Receiver, DAB/DAB+, FM Radio, Internet Radio, USB Player (.mp3)
Line Outputs	1 Stereo (terminal Block)
Network Connectivity	LAN (RJ45), Wi-Fi 802.11a/b/ g/n (2.4GHz and 5GHz bands)



MSMP

MESSAGE SCHEDULER-STREAMER MUSIC
PLAYER

Size	1/3 19" rack, 1U
Third Party/Remote Control	Web Interface / QUESTRA Control
Audio modes	audio message scheduler and streaming media player, local media (USB/MicroSD card), URL sources, Airplay and DLNA streaming
Line Outputs	1 Stereo (RCA)
Network Connectivity	Wired Ethernet and Wifi inter- face for device control and audio streaming capabilities



HPA 2

2-CHANNEL HEADPHONE AMPLIFIER

Size	1/4 19" rack, 1U
Line Inputs	2
Audio modes	Headphone Mode (Mono/ Stereo), HP+Monitor Mode
Line Outputs	2
Headphone Outputs	2x 3,5mm Jack (Front), 2x 6,3mm Jack (Back)



PRE 2

2-CHANNEL MICROPHONE AND LINE MIXER


Size	1/4 19" rack, 1U
Line Inputs	1 Stereo (terminal Block)
Third Party/Remote Control	VCA
Line Outputs	1 Stereo (terminal Block)
Phantom Power	24V



TR (206/212)

AUDIO LINE TRANSFORMER

Size	1/3 19" rack, 1U
Line Inputs	2
Powered Outputs	2x 60W (TR206) / 2x120W (TR212)
Low Impedance Input	2x 80hm/40hm/20hm
High Impedance Outputs	2x 25V/70V/100V



TICA RACK TRAY

19" RACK TRAY FOR TICA® SERIES PRODUCTS

- Mount any combination of TICA® Series products into 1 rack unit
- Marked mounting holes for easy product mounting
- Ventilation holes to keep your system cool
- For quarter, third and half 19 inch width devices

IMA[®] SERIES

INSTALLATION MIXING AMPLIFIERS

Your permanent audio installations require solutions that on the one hand blend discreetly into the background and on the other hand are highly flexible and versatile in their functions. You need to be able to connect different audio sources and manage them, to mute non-priority signals during announcements or emergency calls.

With the IMA[®]-Series, LD Systems presents an all-in-one mixing amplifier-series, which leaves nothing to be desired in terms of quality, design and flexibility. Seamless integration for industrial and commercial applications thanks to the 9.5-inch housing design, a wide range of connectivity options including Bluetooth[®] for wireless audio connection and a multistage priority circuit are just some of the benefits the IMA[®] Series offers. And best of all, the IMA[®]-Series products, are designed to be intuitive and easy to use for everyone.



LINE INPUT FOR EMERGENCY
SIGNAL WITH CONTACT CLOSURE

SWITCHABLE CHIME FEATURE
IN MIC/LINE 1 CHANNEL

4 PRIORITY LEVELS
FOR COMPREHENSIVE
INTEGRATION OPTIONS

BALANCED AUX LINE OUTPUT
WITH MUSIC-MIX SWITCH

**SWITCHABLE AUTO
STANDBY MODE** FOR
REDUCTION OF ENERGY
CONSUMPTION



INTUITIVE CONTROL PANEL DESIGN
WITH CAPACITIVE CONTROLS FOR SELECTING
MUSIC SOURCE AND BLUETOOTH PAIRING



Find out more about our **IMA SERIES**
ld-systems.com/IMA



IMA® 240

INSTALLATION MIXING AMPLIFIER 240W

RMS Power	240 W (Continuous sine wave 1kHz, 4 ohm load)
Amplifier Outputs	High-Z: 70V or 100V; Low-Z: 4 Ohms minimum
Dimensions (W x H x D)	210 x 95 x 267 mm 8.3 x 3.7 x 10.5 inch
Weight	3.5 kg / 7.7 lbs



IMA® 120

INSTALLATION MIXING AMPLIFIER 125W

RMS Power	125 W (Continuous sine wave 1kHz, 4 ohm load)
Amplifier Outputs	High-Z: 70V or 100V; Low-Z: 4 Ohms minimum
Dimensions (W x H x D)	210 x 95 x 267 mm 8.3 x 3.7 x 10.5 inch
Weight	3 kg / 6.6 lbs



IMA® 60

INSTALLATION MIXING AMPLIFIER 65W

RMS Power	65 W (Continuous sine wave 1kHz, 4 ohm load)
Amplifier Outputs	High-Z: 70V or 100V; Low-Z: 4 Ohms minimum
Dimensions (W x H x D)	210 x 95 x 267 mm 8.3 x 3.7 x 10.5 inch
Weight	2.4 kg / 5.3 lbs



IMA® 30

INSTALLATION MIXING AMPLIFIER 35W

RMS Power	35 W (Continuous sine wave 1kHz, 4 ohm load)
Amplifier Outputs	High-Z: 70V or 100V; Low-Z: 4 Ohms minimum
Dimensions (W x H x D)	210 x 95 x 267 mm 8.3 x 3.7 x 10.5 inch
Weight	2.4 kg / 5.3 lbs



IMA® RK

RACK- AND UNDER TABLE MOUNT KIT FOR IMA®

- Rack and under table mount kit for IMA series mixing amplifiers
- For mounting one single unit or two units together
- One IMA device in a 19-inch rack (2 RU)
- One IMA device under a table, a shelf, or under a counter
- Two IMA devices together in a 19-inch rack (2 RU)
- Seven-piece installation set including screws



PRE ST 1

4-CHANNEL STEREO MIXER PREAMPLIFIER

Emergency input	1 balanced line input
Mic/ line inputs	2
Music sources	2 unbalanced stereo line inputs, Bluetooth 4.0
Dimensions (W x H x D)	210 x 95 x 267 mm 8.3 x 3.7 x 10.5 inch
Weight	2.08 kg / 4.6 lbs

IPA SERIES

INSTALLATION POWER AMPLIFIERS

Whether in hotels, schools, houses of worship or airports, the future is audio solutions that grow and adapt to new conditions. The IPA Series DSP-based installation amplifiers offer four-channel, powerful class-D power amplifiers with direct access to the most typical basic DSP controls. The IPA Series is already prepared for remote operation with the future remote panels and paging microphones from LD Systems. An additional expansion slot guarantees a high level of future-proofing. The configuration of the IPA installation amplifiers is even more flexible thanks to the optional Ethernet card, for example when the room layout is changed or when there are fluctuating numbers of attendees. The Ethernet+Dante card also offers Dante audio networking capabilities in order to transmit high quality, uncompromised audio with almost no latency via a standard IP network. This solution guarantees access to a wide range of Dante-enabled devices for all conceivable applications.

SLOT FOR OPTIONAL EXPANSION CARDS
FOR ETHERNET OR ETHERNET + DANTE

STEREO/PARALLEL/BRIDGE MODE
SELECTOR PER PAIR OF CHANNELS

DSP PRESETS WITH HPF
AND LPF WHICH CAN BE
ACTIVATED VIA DIP SWITCHES

4 BALANCED LINE INPUTS AND
4 SPEAKER OUTPUTS WITH
TERMINAL BLOCK CONNECTIONS

SPEAKER PROTECTION
CIRCUITS

USER-FRIENDLY FRONT PANEL
WITH SIGNAL, LIMIT, PROTECTION, MUTE
AND BRIDGE MODE LEDS PER CHANNEL



OPTIONAL RACK
RAILS AVAILABLE

Find out more about our **IPA SERIES**
ld-systems.com/IPA





IPA 424 T

4-CHANNEL DSP INSTALLATION AMPLIFIER
4 X 240 W @ 4 OHM / 70V / 100V

Rated output power (1kHz @ 4 Ohms)	4 x 240 W (1.5 seconds sine burst)
Rated output power (1kHz @ 8 Ohms, bridged)	2 x 490 W (1.5 seconds sine burst)
Expansion Slot	For optional Ethernet, or Ethernet + Dante cards
Dimensions (W x H x D)	483 x 44.5 x 425 mm 19 x 1.75 x 16.7 inch
Weight	11.36 kg / 25 lbs



IPA 412 T

4-CHANNEL DSP INSTALLATION AMPLIFIER
4 X 120 W @ 4 OHM / 70V / 100V


Rated output power (1kHz @ 4 Ohms)	4 x 240 W (1.5 seconds sine burst)
Rated output power (1kHz @ 8 Ohms, bridged)	2 x 490 W (1.5 seconds sine burst)
Expansion Slot	For optional Ethernet, or Ethernet + Dante cards
Dimensions (W x H x D)	483 x 44.5 x 425 mm 19 x 1.75 x 16.7 inch
Weight	8.7 kg / 19.2 lbs



X-EDAI

ETHERNET & DANTE AUDIO INTERFACE EXPANSION CARD
FOR IPA SERIES

Software	QUESTRA®
Dante Channels	4 x 4
Dimensions (W x H x D)	82.5 x 36.5 x 76.3 mm 3.25 x 1.44 x 3 inch
Weight	0.5 kg / 1.1 lbs



X-ECI

ETHERNET CONTROL INTERFACE CARD FOR IPA SERIES

Software	QUESTRA®
Dimensions (W x H x D)	82.5 x 36.5 x 76.3 mm 3.25 x 1.44 x 3 inch
Weight	0.5 kg / 1.1 lbs



+



=



QUESTRA®

IPA SERIES

X EDAI OR X ECI



Set up your system from one place

Tired of opening up different programs to configure all your equipment? Questra is a single application for PC that lets you configure all Adam Hall Questra compatible products from one program. Use online or offline; adjust settings, create presets and configure remote control using a consistent, easy to use interface.



Find out more about our **QUESTRA®**
Id-systems.com/QUESTRA

ZONE X SERIES

HYBRID ARCHITECTURE DSP MATRIX

In hotels, restaurants, conference centers, churches – wherever signals need to be dynamically distributed and switching processes controlled, a ZONE X DSP matrix processor makes sure everything runs smoothly. You can conveniently and concisely plan events and rely on seamless processes with comprehensive automation. The ZONE X processor becomes the brain of your installation, so to speak, just waiting for your commands.



12 BALANCED AUDIO MIC/LINE INPUTS



**12 BALANCED LINE OUTPUTS
& 8 GPI/GPO LOGIC-PORTS**

ETHERNET + DANTE CARD OPTIONALLY AVAILABLE

**HYBRID ARCHITECTURE DSP PROCESSOR
WITH PRACTICAL TEMPLATES**



40-BIT FLOATING POINT DSP ENGINE

**ANALOG DEVICES DUAL CORE SHARC+
AND ARM CORTEX A5 PROCESSOR**



Find out more about our **ZONE X SERIES**
[id-systems.com/ZONEX](https://www.id-systems.com/ZONEX)



EXTENSIVE SYSTEM CONTROL IN MULTI-ZONE INSTALLATIONS

ZONE X 1212 (D)

HYBRID ARCHITECTURE DSP MATRIX - 12 IN / 12 OUT
(WITH DANTE STANDARD)

Audio inputs	12 balanced mic/line inputs + 1 remote bus audio input
Audio outputs	12 balanced line outputs
DSP	40-bit floating point Analog Devices Dual-core SHARC+ processor
Dimensions (W x H x D)	483 x 44.5 x 315 mm 19 x 1.75 x 12.4 inch
Weight	4 kg / 8.8 lbs

Features

- DSP processor with hybrid architecture that allows users to adapt to different installation requirements via templates
- 40-bit floating point DSP engine with Analog Devices dual core SHARC+ and ARM Cortex A5 processor
- New generation Linux operating system
- Premium microphone preamplifiers and high resolution 32 bit-AD/DA converters
- 12 balanced audio mic/line inputs with 48V phantom power selection per channel
- 12 balanced line outputs
- 8 GPI and 8 GPO logic ports
- Ethernet + Dante interface for remote control via the universal control software Xilica Designer and integration of Dante-compatible devices
- Integrated event scheduler

the brain of your installation



U500[®] SERIES

WIRELESS MICROPHONE SYSTEMS

The U500[®] Series wireless systems have been developed based on user feedback to provide technically advanced yet affordable wireless microphones and in-ear monitoring systems tailored to the needs of professional users. Whether for vocals, instruments or wireless in-ear monitoring, our versatile sets meet your expectations for premium sound, reliability and ease of use.

SOUND QUALITY WITH UP TO 100 METERS OR 300 FEET OF REACH

UP TO 12 SYSTEMS SIMULTANEOUSLY

ONE BODYPACK, WIDE RANGE WITH MINI XLR INPUT, WITH A THREE-POSITION LEVEL SWITCH

INTERCHANGEABLE MIC HEADS



Find out more about our **U500** SERIES
ld-systems.com/U500





U5XX* HBH 2

WIRELESS MICROPHONE SYSTEM WITH BODYPACK, HEADSET AND DYNAMIC HANDHELD MICROPHONE

Channels	96 (8 groups of 12 channels)
Frequency response	30 Hz - 16 KHz Headset: 20 Hz - 20 KHz Microphone: 60 Hz - 16 KHz
Rated HF output power	Variable (2, 10, 30 mW)



U5XX* BPHH

WIRELESS MICROPHONE SYSTEM WITH BODYPACK AND HEADSET

Channels	96 (8 groups of 12 channels)
Frequency response	30 Hz - 16 KHz Headset: 70 Hz - 16 KHz
Rated HF output power	Variable (2, 10, 30 mW)



U5XX* HHD

WIRELESS MICROPHONE SYSTEM WITH DYNAMIC HANDHELD MICROPHONE

Channels	96 (8 groups of 12 channels)
Frequency response	60 Hz - 16 KHz
Rated HF output power	Variable (2/10/30mW)



U5XX* HHD 2

DUAL WIRELESS MICROPHONE SYSTEM WITH 2X DYNAMIC HANDHELD MICROPHONE

Channels	96 (8 groups of 12 channels)
Frequency response	60 Hz - 16 KHz
Rated HF output power	Variable (2/10/30mW)



WS 100 DA

DIRECTIONAL ANTENNA FOR SETTING UP LARGER SYSTEMS


Frequency band	500 - 900 MHz
Antenna gain	7 dBi
Antenna connector	BNC



WS 100 AB

ANTENNA BOOSTER

Frequency band	500 - 900 MHz
Signal gain	13 dB
Antenna output connection	BNC




WIN 42 AD

4-WAY ANTENNA SPLIT BOX

Frequency band	500 - 900 MHz
Signal gain	3 dB
Antenna output connection	BNC

* WHAT FREQUENCY DO YOU REQUIRE?

- 470 - 490 MHz: **U504.7 (only available in USA)**
- 514 - 542 MHz: **U505.1 (only available in USA)**
- 548 - 607 MHz **U505**
- 655 - 679 MHz **U506**
- 823 - 832 MHz / 863 - 865 MHz **U508**
- 1785 - 1800 MHz **U518**




U500® CS4

4-CHANNEL WIRELESS CONFERENCE SOLUTION

Designed around you and for you, our engineering and development put their focus on professional users to create a wireless conference system for effective communication and interaction. Providing advanced technology and superb speech intelligibility, the U500® is a fully featured, elegant solution. This user-friendly system makes your job easier and conventions, meetings and discussions a success.

HIGHPASS FILTER
PREVENTS BOOMINESS UP CLOSE

INDIVIDUAL XLR OUTPUTS
FOR EACH OF THE 4 CHANNELS



AUTO AND MANUAL GATE
FOR NOISE CONTROL

RECEIVER CASCADING
UP TO FIVE
MICRO-PHONE UNITS

REMOVABLE GOOSENECK MIC

PILOT TONE FOR NOISE
FREE TRANSMISSION

EXTERNAL CONTROL
VIA REMOTE SYSTEMS

Find out more about our **U500** SERIES
ld-systems.com/U500



U500[®] CONFERENCE SOLUTION



U50X^{*} CS4

4-CHANNEL WIRELESS CONFERENCE SYSTEM

CONFERENCE RECEIVER

Modulation type	FM
Groups	6
Channels	60 (6 x 10)
Antenna inputs	2
Antenna connectors	BNC
Frequency response	60 - 16,000 Hz
Noise reduction	adjustable squelch (10 steps)
Signal-to-noise ratio	> 100 dB
Audio outputs balanced	4 x XLR
Audio outputs mix balanced	XLR
Max. output level	+12 dBu
Controls	power on/off, digital encoder, RX 1 - 4 quick access buttons
Indicators	OLED display
Dimensions (W x H x D)	484 x 44 x 243 mm 19.1 x 1.7 x 9.6 inch
Weight	2.45 kg / 5.4 lbs

CONFERENCE MICROPHONE

Groups	6
Channels	60 (6 x 10)
Inputs	XLR
Frequency response	60 - 16,000 Hz
Signal-to-noise ratio	> 100 dB
Rated HF output power	10 mW
Controls	low cut, power / mute, gain
Indicators	LED, OLED display
Dimensions (W x H x D)	115 x 54 x 135 mm 4.5 x 2.1 x 5.3 inch
Weight	0.72 kg / 1.59 lbs



U500[®] RK

RACKMOUNT KIT FOR U500[®] RECEIVER

Product type	Wireless Microphone System Accessories
Surface	Powder coated
Weight	0.2 kg / 0.44 lbs



* WHAT FREQUENCY DO YOU REQUIRE?

- 554 - 586 MHz: **U505 CS4**
- 662 - 694 MHz: **U506 CS4**
- 823 - 832 MHz / 863 - 865 MHz: **U508 CS4**

QUESTRA®

simply powerful.

DESIGN & MANAGEMENT SOFTWARE FOR NETWORKED LD SYSTEMS INSTALLATION SOLUTIONS

Meet QUESTRA® - the design and management software for networked LD Systems installation solutions. QUESTRA® enables a streamlined configuration of LD Systems devices and the design of custom user panels that can be controlled on both Windows computers and Android or iOS portable devices.



for Windows



for control panels

WHAT IS QUESTRA®?

With QUESTRA® you gain access to the full DSP capabilities of LD Systems' audio installation devices. It allows you to configure audio networks, small and large, but also to manage every single device and control it from a single application.

PLANNING A PROJECT




Plan and prepare system configurations right from early stages of your install project 0150 even before installing any hardware on site. Quickly create end-user interfaces to demonstrate to customers before they buy. With QUESTRA you're in pole position to win that next pitch.

PROJECT DEPLOYMENT

Deploying your new system is just a few clicks away. Simply upload your offline configuration to all the online devices on the network, fine-tune the project and device settings and you're done! QUESTRA® makes your work easier with its intuitive User Interface, clearly structured menus and quickly accessible settings.

PROJECT ADMINISTRATION

QUESTRA® puts you in control of all your installation projects. Create users, assign specific roles, limit the access to certain functions and ensure critical network settings cannot be modified. Easily create and manage device presets for different user applications for users to trigger using QUESTRA® Panels. With remote access, you can monitor your installation and provide maintenance from anywhere, at any time.



QUESTRA®

Management of networked LD Integrated Systems solutions



QTP 5

QUESTRA TOUCHSCREEN DISPLAY 5-INCH
WITH ANDROID 11 AND POE

Mounting options	86-Type Electrical Box, EU - flush-mounted box
Power supply	External power supply unit 12 V DC 2 A (optionally available), IEEE 802.3 at compliant, PoE (Power over Ethernet)
Dimensions (W x H x D)	145.7 mm x 84 mm x 38 mm 5.74 inch x 3.3 inch x 1.5 inch
Weight	0.32 kg / 0.7 lbs



QTP 8

QUESTRA TOUCHSCREEN DISPLAY 8-INCH
WITH ANDROID 11 AND POE

Mounting options	86-Type Electrical Box, EU - flush-mounted box, US - 2 - gang-electrical Box
Power supply	External power supply unit 12 V DC 2 A (optionally available), IEEE 802.3 at compliant, PoE (Power over Ethernet)
Dimensions (W x H x D)	200 mm x 124.6 mm x 37.7 mm 7.87 inch x 4.9 inch x 1.48 inch
Weight	0.34 kg / 0.75 lbs

Have a closer look
at QUESTRA® in our
explainer video



Find out more about **QUESTRA**
ld-systems.com/QUESTRA

CONTRACTOR SERIES

PROFESSIONAL INSTALLATION SPEAKERS

The professional installation monitors of the CONTRACTOR® Series can be perfectly combined thanks to their uniform look and are the elegant solution for unobtrusive audio systems. The range includes in-wall speakers for ceilings and walls, frameless in-wall speakers as well as wall mount models. The ceiling and in-wall speakers are available in white, the wall mount speakers in black or white. All models of the CONTRACTOR® Series have an extended frequency response with a high sound quality and speech intelligibility. They are ideal for permanent installations in hotels, restaurants, bars, theatre lobbies, shopping centres and AV systems.



Find out more about our **CONTRACTOR SERIES**
id-systems.com/CONTRACTOR



CFL 52(100V) / CFL 62 (100 V)

5.25" / 6.5" FRAMELESS 2-WAY IN-WALL SPEAKER (100 V)

Type	Ceiling-mounted loudspeaker
Low-impedance rated load (RMS)	CFL 52 (100 V): 40 W; CFL 62 (100 V): 60 W
Depth	CFL 52 (100 V): 81 mm / 3.19 inch CFL 62 (100 V): 86 mm / 3.39 inch
Diameter	CFL 52 (100 V): 204 mm / 8.03 inch CFL 62 (100 V): 234 mm / 9.12 inch
Weight	CFL 52 (100 V): 1.225 kg / 2.7 lbs CFL 62 (100 V): 1.56 kg / 3.4 lbs



CICS 52 (100 V) / CICS 62 (100 V)

5.25" / 6.5" 2-WAY IN-WALL SPEAKER (100 V)

Type	Ceiling-mounted loudspeaker
Low-impedance rated load (RMS)	CICS 52 (100 V): 40 W; CICS 62 (100 V): 60 W
Depth	CICS 52 (100 V): 92 mm / 3.62 inch CICS 62 (100 V): 100 mm / 3.94 inch
Diameter	CICS 52 (100 V): 202 mm / 7.95 inch CICS 62 (100 V): 233 mm / 9.17 inch
Weight	CICS 52 (100 V): 1.31 kg / 2.9 lbs CICS 62 (100 V): 1.795 kg / 3.96 lbs



NEW CE C6 / CE C8

FRAMELESS 6" / 8" CEILING LOUDSPEAKER 100V

Type	Ceiling-mounted loudspeaker
Low-impedance rated load (RMS)	CE C6: 6 W; CE C8: 10 W
Depth	CE C6: 74 mm / 2.91 inch CE C8: 90 mm / 3.54 inch
Diameter	CE C6: 186 mm / 7.32 inch CE C8: 232 mm / 9.13 inch
Weight	CE C6: 0.76 kg / 1.68 lbs CE C8: 0.76 kg / 1.68 lbs



CWMS 42 (100 V) / CWMS 52 (100 V)

4" / 5.25" 2-WAY WALL MOUNT SPEAKER 100 V

Type	Ceiling-mounted loudspeaker
Low-impedance rated load (RMS)	CFL 52 (100 V): 40 W; CFL 62 (100 V): 60 W
Depth	CFL 52 (100 V): 81 mm / 3.19 inch CFL 62 (100 V): 86 mm / 3.39 inch
Diameter	CFL 52 (100 V): 204 mm / 8.03 inch CFL 62 (100 V): 234 mm / 9.12 inch
Weight	CFL 52 (100 V): 1.225 kg / 2.7 lbs CFL 62 (100 V): 1.56 kg / 3.4 lbs



NEW CE H30

OUTDOOR HORN LOUDSPEAKER

Type	Horn loudspeaker
Low-impedance rated load	30 W (RMS)
Dimensions (W x H x D)	205 x 280 x 285 mm 8.07 x 11.02 x 11.22 inch
Weight	2.21 kg / 4.87 lbs



NEW CE P10

10W PROJECTOR LOUDSPEAKER

Type	Wall-mounted speaker
Low-impedance rated load	60 W (RMS)
Dimensions (W x H x D)	305 x 218 x 76 mm 12 x 8.6 x 2.99 inch
Weight	1.69 kg / 4.19 lbs



NEW CE PB10

10W BI-DIRECTIONAL LOUDSPEAKER

Type	Wall- and ceiling speaker
Low-impedance rated load	10 W (RMS)
Dimensions (W x H x D)	138 x 138 x 200 mm 5.4 x 5.4 x 7.9 inch
Weight	1.7 kg / 3.75 lbs



NEW CE 360

360-DEGREE PENDANT LOUDSPEAKER

Type	Pendant loudspeaker
Low-impedance rated load	20 W (RMS)
Diameter	254 mm / 10 inch
Weight	2.42 kg / 5.34 lbs



CWS 62

6.5" 2-WAY IN-WALL SPEAKER

Type	Wall-mounted
Low-impedance rated load	60 W (RMS)
Dimensions (W x H x D)	305 x 218 x 76 mm 12 x 8.6 x 2.99 inch
Weight	1.69 kg / 4.19 lbs



COGS 52

5.25" OUTDOOR GARDEN SPEAKER

Type	Outdoor loudspeaker
100 V Inputs	2 W, 4 W, 8 W, 16 W, 32 W
Height	372 mm / 14.65 inch
Diameter	345 mm / 13.58 inch
Weight	3.88 kg / 8.55 lbs

PROJECT REFERENCES

BY ADAM HALL INTEGRATED SYSTEMS

For all types of installation projects, the Adam Hall Group provides high quality solutions to engage and delight your audience. From hospitality and retail to conferencing, music venues and more, we have decades of experience in developing and delivering innovative and reliable installation products.

With our extensive expertise, we are able to provide technical and logistical planning support and offer a comprehensive in-house repair service. We also run training courses through the Adam Hall Academy for those who want to learn more about sound.



SOUND FOR THE PALACE

LD SYSTEMS AT THE W BUDAPEST HOTEL

151 rooms in the historic Drechsler Palace, directly on the famous Andrassy Avenue shopping boulevard – since the opening of the W Budapest in the summer of 2023, the Hungarian capital has a new hotel highlight in the luxury segment. After an extensive restoration phase, the 5-star hotel of the Marriott chain delights with its mix of historical elements and modern design. To welcome the guests of the W Budapest with appropriate and versatile audio that can do more than just background music, the contracted integrator ComplexIT relied on a combination of CURV 500 portable array systems and active subwoofers from the MAUI G3 series.



Learn more:
blog.adamhall.com

MULTI-ZONE AUDIO SYSTEM

LD SYSTEMS AT ARCA RESORT IN ROMANIA

If you want to eat particularly fresh fish in Romania, you can't avoid the ARCA Resort. Located directly at a large fish pond, the owners of ARCA run a high-quality fish restaurant with its own fish farm. But the building complex offers its guests much more than that: weddings and corporate events, tiny houses on the shore of the lake and a park with playgrounds and sports fields for children and adults. In order to provide the multifunctional location with audio signals as flexibly as possible, integrators Direct Sound took advantage of the extended closure period during the COVID pandemic to install a multi-zone audio system based entirely on LD Systems solutions.



Learn more:
blog.adamhall.com



About our **mission.**

RELIABILITY

Regardless of which concert or event, whether on stage or at a conference, you have to instinctively be able to rely on your sound system. That's why LD Systems® continues to pride itself on delivering high-quality materials and long-lasting workmanship.



SOUND PERFORMANCE

Product developers at LD Systems take great care to ensure that the sound you've got in mind becomes a reality. From tweeters to subwoofers, or from mobile PAs to installed systems, our goal is to always represent the latest state of sound technology.



USER-FRIENDLINESS

LD Systems® puts the user first, meaning that simple, intuitive, and efficient operation is already factored in at an early stage during development. From ergonomic handles to easily readable LED displays.



DESIGN LANGUAGE

Thanks to its design-award-winning design language, LD Systems® products are not only a pleasure to be heard but a beauty to behold. The unmistakable LD Systems® Angle, for example, is used time and time again and gives products their special look.



PASSION

We are dedicated to achieving excellence with remarkable engineering and measurement capability - like the passion that grips a musician on stage, the engineers and designers at LD Systems® are enthusiastic to bring the highest standards in sound and design to our products - **LD Systems® engineered in Germany.**



**Interested in products or need a quote
for your installation project?**

Please contact our sales department or make an
appointment with our sales representatives.



Adam Hall GmbH
Adam-Hall-Str. 1 | 61267 Neu-Anspach | Germany
sales@adamhall.com | **+49 6081 9419-300**

your sound.
our mission.



facebook.com/ldsystems
instagram.com/ld_systems_official
youtube.com/ldsystemsvideos

ld-systems.com

LD Systems is a brand of the Adam Hall Group
© 2024 Adam Hall Group. All rights reserved